

Belt conveyor

To directly connect your binding stations



*Note: the control set displayed on the picture is not a part of the [full set](#).

Belt conveyor – full set

Belt conveyor was designed to transport semi-finished and finished products. It is most optimal for transport between bookbinding operations. Conveyor belts are the most versatile solution for book handling.

The conveyor has a possibility to customize its height from 740mm to 1095mm, and length starting from 1200mm to the iterations of 1200mm. We offer belts in 3 options, defined by the grip level. All extensions/modifications are easily accessible, because we offer [all separate components](#) on our website.

Specifications

Belt conveyor – full set		
Full set conveyor parameters		
Length	1000/1200/1700/2500mm	
Width	Direct drive - 525mm Drive with a belt gear - 446mm Omega drive - 525mm	
Height	780 - 1135mm	
Weight (1000/1200/1700/2500mm)*	25-28 / 26-29 / 31-34 / 35-38 kg	
Bare belt conveyor parameters		
Length	1000/1200/1700/2500mm	
Width	Direct drive - 510mm Drive with a belt gear - 432 mm Omega drive - 510 mm	
Height	Direct drive - 196 mm Drive with a belt gear - 387 mm Omega drive - 217mm	
Weight (1000/1200/1700/2500mm)*	16-19 / 17-20 / 21-24 / 26-29 kg	
Belt parameters		
Low grip belt	https://urlzs.com/opx6B	
Normal grip belt	https://urlzs.com/kMBWB	
High grip belt	https://urlzs.com/fUonc	
Conveyor legs parameters		
Width	450mm	
Height	740 - 1096mm	
Load capacity	5kg	
Leg support bar parameters		
Short	Length	1700mm
	Weight	2kg
Long	Length	2500mm
	Weight	4kg
Electrical supply data		
Voltage	3~ 230V AC 50Hz	
Power input	500W	

*Depends on a drive type